

DATA SHEET

Dimensions (L x W x H), mm	655×900×1430	
Weight, kg	130	
Supply voltage, V	400	
Supply mains type	Three phase	
Drive power, kW	7.5	
Quantity of storage batteries (not included into supply slip)	2 similar lead-acid by 12V	
Battery capacity	45Ah min.	
Storage battery automatic charging	Available	
Rated voltage of the diagnosed units, V	12, 24	
Maximum overall length of the diagnosed unit, mm (m)	410 (0,41)	
Alternator diagnostics		
Load, A	12V	300
	24V	150
Verification regime	Automatic/manual	
Load adjustment (0-100%)	Smoothly	
Drive speed, rpm	0-3000	
Drive speed adjustment	Smoothly	
Drive type (alternator drive)	V-belt drive/Poly V-belt drive	
Types of diagnosed alternators	12V	Lamp, SIG, RLO, RVC, C KOREA, P-D, C JAPAN, COM (LIN, BSS), VALEO I-STAR, STAR
	24V	Lamp, COM (LIN)
Starter diagnostics		
Power of diagnosed starters, kW	up to 11	
Measured parameters	The charts displaying the operation starting mode, voltage variations and voltage current on the terminals: K30, K50 и K45	
Storage battery diagnostics		
Types of diagnosed storage batteries	Any lead-acid storage batteries 12V	
Measured parameters	Capacity	
Additional features		
Display	Touch Screen 12"	
Software update	Available	
Alternator database	Available	
Diagnostics results storage	Available	
Printing	Available	
Internet connection	Wi-Fi (802.11 a/b/g/ac), Ethernet	
Connection of peripheral devices	2 x USB 2.0	