

DATA SHEET

Dimensions (L x W x H), mm		655×900×1430
Weight, kg		100
Supply voltage, V		400
Supply mains type		Three phase
Drive power, kW		4
Quantity of storage batteries (not included into supply slip)		2 similar lead-acid by 12V
Battery capacity		Capacity from 45 up to 60 A-h and dimensions (L x W x H) not exceeding 207×175×175 mm
Storage battery automatic charging		Available
Rated voltage of the diagnosed units, V		12, 24
Alternator diagnostics		
Load, A	12V	150
	24V	75
Load adjustment (0-100%)		Smoothly
Drive speed, rpm		0-3000
Drive speed adjustment		Smoothly
Drive type (alternator drive)		V-belt drive/Poly V-belt drive
Types of diagnosed alternators	12V	Lamp, SIG, RLO, RVC, C KOREA, P-D, C JAPAN, COM (LIN, BSS), VALEO I- StARS
	24V	Lamp, COM (LIN)
Starter diagnostics		
Power of diagnosed starters, kW		up to 11
Measured parameters		The charts displaying the operation starting mode, voltage variations and current on the terminals: K30, K50 и K45
Voltage regulator diagnostics		
Engine rotation imitation, rpm		from 0 up to 6000
Voltage regulator load imitation, %		from 0 up to 100
Types of diagnosed voltage regulators	12V	Lamp, SIG, RLO, RVC, C KOREA, P-D, C JAPAN, COM (LIN, BSS)
	24V	Lamp, COM (LIN)
Optionally		
Display		Touch Screen 7"
Software update		Available
Alternator database		Available
Voltage regulator database		Available
Diagnostics results storage		Available
Printing		Available